According to the OSHA Hazard Communication Standard (29 CFR 1910.1200)



ADEKA ULTRASEAL

\_Date of issue : November/30/2015

## P-201A

SDS No.: US-S-05921

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ADEKA ULTRASEAL P-201A

1.2. Relevant identified uses of the substance or mixture and uses advised against<br/>Relevant usesRelevant usesWater stop for construction use

## 1.3. Details of the supplier of the safety data sheet

## Manufacturer:

ADEKA CORPORATION 2-35, HIGASHI-OGU 7-CHOME, ARAKAWA-KU, TOKYO 116-8554, JAPAN <u>TEL: 81-3-4455-2843</u> <u>FAX: 81-3-3809-8240</u>

## Distributor:

OCM INC. 1215 Henri Drive Wauconda. IL 60084 <u>TEL:866-457-5710</u> <u>FAX: 847-462-4259</u>

**1.4. Emergency telephone number** 

<u>TEL:866-457-5710</u> (9:00am - 5:00pm EST, Monday –Friday (excluding holidays))

## **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

Classification according to OSHA Hazard Communication Standard (29 CFR 1910.1200-2012) [GHS]:

Classification
Acute tox. Inhal : 4
. Resp Sens : 1
Carc. : 2
STOT. RE : 2

## 2.2. Label elements

Labelling according to OSHA Hazard Communication Standard (29 CFR 1910.1200) [GHS] :

Symbols	
Signal word	Danger

According to the OSHA Hazard Communication Standard (29 CFR 1910.1200)



ADEKA ULTRASEAL

Date of issue : November/30/2015

## P-201A

SDS No.: US-S-05921

Hazard Statements	Harmful if inhaled May cause allergy or asthma symptoms or breathing difficulties if Inhaled. Suspected of causing cancer May cause damage to organs(inhalation organs, lung) through prolonged or repeated exposure
	Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray In case of inadequate ventilation wear respiratory protection Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapours/spray IF INHALED : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell IF INHALED : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms call a POISON CENTER or doctor/ physician. IF exposed or concerned : Get medical advice/attention. Get medical attention/advice if you feel unwell. Store locked up. Dispose of contents/container in accordance with local/regional/national/ international regulations.

## 2.3. Unclassified hazards: None

## 2.4. Percentage of ingredients with unknown toxicity: None

## **SECTION 3: Composition/information on ingredients**

Product-type: mixture

Name	%	CAS No.	Classification according to OSHA HCS (29 CFR 1910.1200)
Urethane prepolymer	45~55	Trade secret	-
Inorganic filler	25~35	Trade secret	-
Aliphatic hydrocarbon	10~20	Trade secret	-
Silica ( amorphous )	5~10	7631-86-9	-
Titanium dioxide	1~5	13463-67-7	-

According to the OSHA Hazard Communication Standard (29 CFR 1910.1200)



## ADEKA ULTRASEAL

Date of issue : November/30/2015

## P-201A

SDS No.: US-S-05921

Benzene, 1,1'-methylenebis [4-isocyanato-	<0.5	101-68-8	Acute tox. Inhal : 4, Skin Irrit : 2 Resp Sens : 1, Eye Irrit : 2 Skin Sens : 1, Carc. : 2 STOT. RE : 2, STOT. RE : 3
--	------	----------	--

## **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

## Skin contact

Wash off immediately with plenty of soap and water. Take all contaminated clothing off immediately. Seek medical advice if irritation develops.

#### Eye contact

Immediately flush with large quantities of clean water for at least 15 minutes and call a physician.

#### Inhalation

Move affected person to fresh air. In case of exposure to respiratory system or mucous membranes, or if you feel unwell or in case of prolonged exposure, get medical attention.

#### Ingestion

Do not induce vomiting. See a physician immediately.

#### Note to physician

None

4.2. Most important symptoms and effects, both acute and delayed

No data available

## 4.3. Indication of any immediate medical attention and special treatment needed

No data available

## **SECTION 5: Fire-fighting measures**

## 5.1. Extinguishing media

Dry sand, foam, carbon dioxide or dry chemical agents.

## 5.2. Specific hazards arising from the mixture

Smoke, fumes, oxides of carbon and NOx.

## 5.3. Special protective equipment and precautions for firefighters

Firemen should wear normal protective equipment (full bunker gear) and positive-pressure self-contained

According to the OSHA Hazard Communication Standard (29 CFR 1910.1200)



## ADEKA ULTRASEAL

Date of issue : November/30/2015

## P-201A

SDS No.: US-S-05921

breathing apparatus.

## **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

Clean-up personnel should wear protective clothing and equipment to prevent inhalation of dusts and skin and eye contact.

## 6.2. Environmental precautions

Do not flush into the sewer.

## 6.3. Methods and material for containment and cleaning up

Carefully collect the spilled material and place in a bucket. The area should be thoroughly cleaned.

## 6.4. Reference to other sections

See Section 8+13

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

Avoid contact with eyes. Keep container closed. Use with adequate ventilation. Wash thoroughly after handling. Avoid prolonged or repeated breathing of vapour. Avoid prolonged or repeated contact with skin. Do not allow it to reach to the waterways.

Avoid vapor formation and ignition sources.

## 7.2. Conditions for safe storage, including any incompatibilities

Store away from heat / moisture / strong oxidizing agents.

## 7.3. Specific end use(s)

None

## **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

	OSHA	PEL <sup>2)</sup>		ACGIH 1	TLV <sup>3)</sup>	
Name	TWA		STEL		TWA	
	mg/m³	ppm	mg/m³	ppm	mg/m³	ppm
Titanium dioxide	15				10	
Benzene, 1,1'-methylenebis [4-isocyanato-		0.005				0.005

According to the OSHA Hazard Communication Standard (29 CFR 1910.1200)



## ADEKA ULTRASEAL

\_Date of issue : November/30/2015

## P-201A

SDS No.: US-S-05921

## 8.2. Exposure controls

## Appropriate engineering controls

Where this material is not used in a closed system, good enclosure and local exhaust ventilation should be provided to control exposure.

#### Individual protection measures, such as personal protective equipment

Eye/face protection: Safety glasses or splash goggles. Contact lenses should not be worn.

#### Skin protection

Hand protection: Chemical resistant gloves. Wear overall and closed footwear.

Other: No information available

Respiratory protection: If vapors, mists or aerosols are generated, wear an approved respirator.

Thermal hazards: No information available

#### **Environmental exposure controls**

Treat this product in accordance with the directives and regulations in the United States.

## **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Appearance	:	Gray putty
Odor:		Slight odor
Odor thresh	old:	No data available
pH:		No data available
Melting poin	it/freezing point °F (°C):	No data available
Initial boiling	g point and boiling range °F (°C):	No data available
Flash point	°F (°C):	No data available
Evaporation	rate:	No data available
Flammability	y (solid, gas):	No data available
Upper/lower flammability or explosive limits:		No data available
Vapor press	ure (kPa):	No data available
Vapor densi	ty:	No data available
Relative den	isity:	1.25 at 77°F (25°C) <sup>1)</sup>
Solubility	water solubility:	No data available
	fat solubility:	No data available
Partition coefficient (n-octanol/water):		No data available
Auto-ignitio	n temperature:	No data available
Decomposition temperature:		No data available

According to the OSHA Hazard Communication Standard (29 CFR 1910.1200)



## ADEKA ULTRASEAL

Date of issue : November/30/2015

## P-201A

SDS No.: US-S-05921

Viscosity (mPa•s):

No data available

## **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

No specific test data related to reactivity available for this product or its ingredients.

#### 10.2. Chemical stability

Stable under normal ambient conditions (ambient temperature)

#### 10.3. Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

#### 10.4. Conditions to avoid

Keep away from heat, moisture and static discharges. Cold condition ( below  $5^{\circ}$ C)

#### 10.5. Incompatible materials

Keep away from oxidizing agents, peroxides and strong acid.

#### 10.6. Hazardous decomposition products

Thermal decomposition or combustion may produce oxides of carbon and oxides of nitrogen.

## **SECTION 11: Toxicological information**

#### 2CTION TT: TOXICOlOgical Information 11.1 Information on toxicological effects

Acute toxicity:	No data available, but may be harmful if swallowed.
Skin corrosion/irritation:	No data available, but may cause skin irritation
Serious eye damage/irritation:	No data available, but may cause eye irritation
Respiratory or skin sensitization:	No data available, but may be harmful if inhaled.
Germ cell mutagenicity:	No data available.
Carcinogenicity:	No data available, but may be suspected of causing cancer
Reproductive toxicity:	No data available
STOT-single exposure:	No data available

According to the OSHA Hazard Communication Standard (29 CFR 1910.1200)



ADEKA ULTRASEAL
-----------------

\_\_\_\_Date of issue : November/30/2015

## P-201A

SDS No.: US-S-05921

STOT-repeated exposure:	No data available but may cause damage to organs through prolonged or repeated exposure
Aspiration hazard:	No data available

## **SECTION 12: Ecological information**

12.1. Toxicity	No data available, but may be harmful to aquatic life
12.2. Persistence and degradability	No data available
12.3. Bioaccumulative potential	No data available
12.4. Mobility in soil	No data available
12.5. Results of PBT and vPvB assessment	No data available
12.6. Other adverse effects	No data available

## **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

**Incineration:** Should be in accordance with local regulations.

**Recycling:** Should be in accordance with local regulations.

Land filling: Should be in accordance with local regulations.

SECTION 14: Transport information 14.1. UN number	See the below table
14.2. UN proper shipping name	See the below table
14.3. Transport hazard class(es)	See the below table
14.4. Packing group	See the below table
14.5. Environmental hazards	See section 14.2 in accordance with UN shipping name
14.6. Special precautions for user	Relevant information under SECTION 6 to 8.

According to the OSHA Hazard Communication Standard (29 CFR 1910.1200)



ADEKA ULTRASEAL

Date of issue : November/30/2015

## P-201A

SDS No.: US-S-05921

## 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

	UN No.	Class	Proper shipping name	Packing group	Marine pollutant
IMDG	None				No
ADR/RID	None				
ICAO/IATA	None				

## **SECTION 15: Regulatory information**

US FEDERAL REGULATION.

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture** Not available.

TSCA:	TSCA INVE		registered 🗌 r	not registered		
SARA TI	TLE III					
SECTION 313 TOXIC CHEMICALS			COMPONEN	CAS RN	Wt%	
		Benzene, 1	,1'-methylenebis [4	-isocyanato-	101-68-8	<0.5
California Prop. 65:			COMPONENT			Wt%
		Benzene, 1	,1'-methylenebis [4	-isocyanato-	101-68-8	<0.5
INTERNAT	IONAL INFO	RMATION:				
CEPA : DSL		⊠ registered	registered		not registered	
REACH	(EU):	🛛 If you require i	nformation, please c	ontact us	] not registere	ed

## **SECTION 16: Other information**

**Reference:** 1) Our testing data

- 2) OCCUPATIONAL SAFETY AND HEALTH STANDARDS (OSHA, 2015)
- Threshold limit values of chemical substances and physical agents and biological exposure indices ACGIH(2015)

Japan: ADEKA CORPORATION <u>TEL: +81-480-85-6001</u> <u>FAX: +81-480-85-5928</u> USA: OCM INC. <u>TEL: 866-457-5710</u> <u>FAX: 847-462-4259</u>

According to the OSHA Hazard Communication Standard (29 CFR 1910.1200)



# ADEKA ULTRASEAL

Date of issue : November/30/2015

## P-201A

SDS No.: US-S-05921

To the best of our knowledge, the information contained herein is accurate. However, neither ADEKA CORPORATION nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.